



OMNI FIT™ high performance connectors are designed for use with both CELLFLEX® (copper) and CELLFLEX® Lite (aluminum) cables. They are designed specifically to provide the highest quality connector-cable interface while simplifying and speeding up connector attachment. All RFS connectors are fully tested for mechanical and electrical compliance to industry specifications.

The 7-16 connector is the most rugged RF connection meeting all requirements even under the most severe environmental conditions.

**FEATURES / BENEFITS**

- Cost effective two-piece design for safe and easy installation
- Robust mechanical design for low and consistent intermodulation performance i.e. keeps the mobile network performance up, reduces the number of dropped calls and avoids revenue losses
- Standard electrical performance for consistent and repeatable VSWR i.e. ensure network system performance
- Waterproof to IP 68 i.e. no downtime risk, secures revenue
- RoHS (EU) compliant i.e. can be used on a global basis



716MR-SCF12-C03

**Technical features**

**GENERAL SPECIFICATIONS**

Transmission Line Type		Coaxial Cable
Cable Size		1/2
Cable Type		Foam Dielectric Superflexible
Model Series		SCF12-50 Series
Connector Interface		7-16
Connector Type		OMNI FIT™ Standard
Sealing Method		O-ring
Gender		Male Right Angle

**ELECTRICAL SPECIFICATIONS**

Nominal Impedance, ohms	Ohm	50
3rd Order IM Product @ 2x20 Watts	dBc	-157 ; typical -160
Maximum Frequency	GHz	6.0
VSWR, Return Loss	VSWR (dB)	0 &lt; f ≤ 1.0 GHz: 1.04 (34.1) 1 &lt; f ≤ 2.2 GHz: 1.07 (29.4) 2.2 &lt; f ≤ 2.7 GHz: 1.09 (27.3) 2.7 &lt; f ≤ 3.7 GHz: 1.13 (24.3) 3.7 &lt; f ≤ 5.0 GHz: 1.25 (19.1) 5.0 &lt; f ≤ 6.0 GHz: 1.30 (17.7)

**MECHANICAL SPECIFICATIONS**

Plating Outer/Inner		Trimetal/Silver
Length	mm (in)	53.7 (2.11)
Outer Diameter	mm (in)	38.7 (1.52)
Weight	kg (lb)	0.136 (0.3)
Inner Contact Attachment		Basket
Outer Contact Attachment		Rigidity impaction




**ACCESSORIES**

Wrench size front	mm (in)	18 (3/4)
Wrench size rear	mm (in)	20 (13/16)
Trimming Tool		TRIM-SET-S12-C02

**TESTING AND ENVIRONMENTAL**

Waterproof Level		IP68
------------------	--	------



716MR-SCF12-C03 Outline drawing

**External Document Links**

[Application Note](#)

[Installation Instruction](#)

**Notes**