

Fiber adapter LC/SC, UPC/APC

Single mode, Multi mode. Simplex / Duplex

Product Features:

- Stainless Steel metal plate
- High precision ceramic sleeve
- Low insertion loss, high return loss
- Free of halogen (LSZH)
- ECS^{DK} = Quality products based on 20 years of experience



Technical data

Specification	Value
Insertion Loss	≤0.2dB
Return loss	UPC: ≥50 dB APC: ≥60 dB MM PC: ≥35 dB
Operating temperature	-40~85°C
Maximum pulling force	LC/SC: 2.0N ~ 5.9N (200gf ~ 600gf)
Flammability	Complies with IEC 61754-4, UL94 V-0 Standard
Polishing	UPC/APC
Compliance	TIA/EIA-604 FOCIS-10 compatible, exceeds TIA/EIA-568-B.3 requirements

Single Mode – 9/125µm



Item nr.	Description	Polish	Color
18323-0004	LC Duplex UPC	UPC	Blue
18324-0004	LC Duplex APC	APC	Green
23647-0004	LC Quad APC	APC	Green
11685-0004	SC Duplex UPC	UPC	Blue
16769-0004	SC Duplex APC	APC	Green
12341-0004	SC Simplex UPC	UPC	Blue
11687-0004	SC Simplex APC	APC	Green

Multimode



Item nr	Description	μm	Color
28060	LC Duplex OM2	62,5/125 μm	Beige
28061	LC Duplex OM3	50/125 μm	Aqua
27554-0004	LC Duplex OM4	50/125 μm	Magenta
28062	LC Duplex OM5	50/125 μm	Lime
28063	SC Duplex OM2	62,5/125 μm	Beige
25577-0004-PK	SC Simplex OM4	50/125 μm	Magenta
27553-0004	SC Duplex OM4	50/125 μm	Magenta